



CLIMBER MAY BE MADE REMOVABLE BY ALLOWING ROOM UNDER BOLT AND ELIMINATING THE FLAT WASHER.

ARM LADDER

REVISION		
REV.	DATE	BY
A	12/17/03	MJB
B	06/012/08	RWP




Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

ARM LADDER

DRAWN	CONNERLEY	DATE	05/08/03	MATERIAL	N/A
APPROVED	JJC	DATE	05/08/03	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	108
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NOTED	1 OF 1	108	B	



MODEL 108

ARM LADDER

Arm ladder support frame shall be constructed with 15/16" [33.27 mm] diameter heavy wall tubing. Support frame shall be fastened to 2 x 6 wood boards sealed and varnished that are mounted to the wall on 22.0" [558.8 mm] centers. Grid rungs shall be 1.0" [25.4 mm] diameter steel tubing space 8.0" [203.2 mm] apart. Recommended height above floor to bottom of support frame is 78.0" [1.98 m].

Hardware for attachment to wall not included.