



TRUSS HEIGHT FEET & (METERS)	DIM "A" Ft.-In. (Meters)	DIM "C" Ft.-In. (Meters)
20 TO 20.9 (6.10-6.39M)	5'-0" (1.52M)	6'-6" (1.98M)
21 TO 21.9 (6.40-6.69M)	5'-11" (1.80M)	6'-6" (1.98M)
22 TO 22.9 (6.70-7.00M)	6'-11" (2.11M)	6'-6" (1.98M)
23 TO 23.9 (7.01-7.31M)	7'-11" (2.41M)	6'-6" (1.98M)
24 TO 24.9 (7.32-7.61M)	8'-11" (2.72M)	6'-6" (1.98M)
25 TO 25.9 (7.62-7.92M)	9'-11" (3.02M)	7'-9" (2.36M)
26 TO 26.9 (7.93-8.22M)	10'-11" (3.33M)	7'-9" (2.36M)
27 TO 27.9 (8.23-8.52M)	11'-11" (3.63M)	7'-9" (2.36M)
28 TO 28.9 (8.53-8.83M)	12'-11" (3.94M)	7'-9" (2.36M)
29 TO 30.0 (8.84-9.14M)	13'-11" (4.24M)	7'-9" (2.36M)

NOTE:
 STANDARD ATTACHMENT HEIGHTS (TRUSS HEIGHTS) FOR MODEL 3107 WELDED UNITS ARE 20 FT. MINIMUM AND 30 FT. MAXIMUM
 CONTACT PERFORMANCE SPORTS SYSTEMS FOR INFORMATION IF TRUSS HEIGHTS ARE NOT WITHIN THIS RANGE.

DIMENSIONS ABOVE ARE ± 1/2"

REVISION		
REV.	DATE	BY
A	10/15/03	JJC
B	12/11/03	JJC
C	02/04/04	MDL
D	06/29/05	DAM
E	12/18/06	WAE
F	05/12/08	RWP

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

FRONT BRACED FRONT FOLD BACKSTOP

DRAWN	CONNERLEY	DATE	04/30/03	MATERIAL	N/A
APPROVED	JJC	DATE	04/30/03	FINISH	N/A
FILE LOC.	Q:\Final Release\Specifications			DWG. NO.	3107
SIZE	SCALE	SHT. NO.	PART NO.		
A	NONE	1 OF 1	3107		
					REV
					F



MODEL 3107

Welded Single Post Front Braced Front Folding Basketball Structure

Recommended Application

This model is designed for those areas not allowing sufficient space behind the backboard for a rear brace. This single post unit can be used at heights from 20' to 30'.

Overhead Structure

Unit shall be supported from 3-1/2" O.D. x 0.120" wall ASTM A-500 Grade B horizontal and 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 vertical structural steel tubing secured to the building with heavy gauge steel stampings or weldments (as required by building conditions). When truss span widths exceed 10'-0", 3-1/2" O.D. x Schedule 40 (0.216") wall ASTM A-500 Grade B will be used for the horizontals. Spans over 14'-0" will use welded bridge pipe.

Backstop

The backstop shall be of a single post design with a main vertical mast made of 6-5/8" O.D. x 0.120" wall ASTM A-500 Grade B structural steel tubing with 2-1/2" x 1-1/2" x 14 gauge (0.083") wall ASTM A-513 rectangular steel tube sway braces miter cut and welded in place to a top horizontal 4" x 1-1/2" x 0.18" web ASTM A-36 steel channel. Main mast will be suspended from superstructure with an offset hanger 3" in front of the pivot point. Units with less than 3" offset will not be approved as equal. Backstop shall be manufactured to allow 6" vertical adjustment for plumbing of the backboard. All fittings shall be heavy gauge steel stampings or weldments. A direct goal attachment is used to transfer stress from the goal to the main mast assembly preventing strain on the backboard.

Front brace shall be 1-7/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tubing attached to the main mast 12" to 18" above the backboard. When truss heights are higher than 27'-0", front brace shall be 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tubing. Folding brace shall be of a jackknife design with an adjustable hinge for easy installation and field adjustment.

Backstop shall be raised and lowered with 1/4" galvanized aircraft cable with a breaking strength of 7000 lbs. Backstop manufactured in accordance with 1994 rule 1, section 8, stating that all parts of the backboard support system shall be at least 6" behind backboard.

All steel has a black powder coat finish, standard. Optional colors are available.

Accessories

Backboards and Goals - See the backboards and goals section in the specification manual.

Backboard Padding - See the accessories section in the specification manual.

Hoists - Electric hoist or manual winch is available on all folding units. See the accessories section in the specification manual.

Certifications

Unit meets all requirements of the NCAA and NFHS. Unit complies with design standards of the California Department of State Architects. Unit is approved by FIBA for international Level 2 competition. Certificate of Approval available.

