



## **MODEL 4500**

### **COLUMN PADDING**

Column padding shall be constructed as a wood backed u-shaped pad with 1" [25.4 mm] nailing lip on top and bottom of each panel for square columns or a wrap-around pad for round columns, using hook and loop fastener straps for attachment to the column. Size must be specified. Pads shall be constructed using the foam of your choice cemented to 7/16" [11.11 mm] oriented strand board. Available foams 2" [50.8 mm] thick 3.5-lbs. density polyurethane or 2" [50.8 mm] thick 6 lbs. density bonded polyurethane foam. Other thicknesses available on request.

Cover material shall be 14-ounce polyester laminated vinyl stapled to backing every two inches. Vinyl to be flame retardant material, which meets NFPA 701, ASTM E84, and CSFM (California State Fire Marshall). Flame retardant vonar® interliner and fire retardant treated plywood backing are also available. Vinyl shall be available in white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, teal and purple.

Custom cutting and fitting of padding may be done in field to insure proper fit. Furring strips by others.

### **ACCESSORIES**

#### **WALL ATTACHMENT TRIMS AND HARDWARE**

Most wall padding may be attached with special attachment trims and hardware. See the wall padding section in the specification manual.