



REVISION		
REV.	DATE	BY
A	10/28/03	MDL
B	01/05/04	MDL
C	01/22/04	MDL
D	03/04/05	ATS
E	06/02/08	RWP
F	06/11/09	RWP



Gared Holdings, LLC  
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**SCHOLASTIC VOLLEYBALL SYSTEM - 1 COURT**

DRAWN	LEWIS	DATE	10/10/03	MATERIAL	N/A
APPROVED	JJC	DATE	10/14/03	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO. 6100	
SIZE	SCALE	SHT. NO.	PART NO.		
A	NONE	1 OF 1	6100	REV F	



## **MODEL 6100**

### **SCHOLASTIC TELESCOPIC VOLLEYBALL SYSTEM**

#### **RECOMMENDED APPLICATION**

Top quality unit for use in facilities requiring product for competitive situations. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

#### **FLOOR SLEEVES AND COVER PLATES**

Please refer to attached specification

#### **UPRIGHTS**

Upright Bottom Post shall be lightweight high strength 3 ½" O.D. aluminum. The upper telescoping adjustable tube shall be 2 7/8" lightweight high strength aluminum. Finish shall be gray anodize. Uprights shall be removable type designed for use with below floor sleeves or above floor T-bases. Uprights shall be provided with adjustable high impact rubber foot to protect finished floors and to allow for additional precise net height adjustment. The uprights will have infinite net height adjustment between 6' to 8' -4" to meet all age group height settings for both men and women.

#### **NET TENSIONER (WINCH)**

The net tensioner shall incorporate a heavy duty, self-locking ratchet mechanism with a compression clutch brake type release. A high tensile nylon strap will be used with the winch to achieve required net tension.

#### **NET**

Net features include 1" diameter wood dowel and 4" square black nylon mesh (250-lbs tensile strength) for excellent performance and durability. Free floating net along 1/8" diameter steel 7 x 19 cable (1,760-lbs. Minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with metallic clips are used to secure net in place. Net shall be 32' length and 39" width. Net perimeter shall have a 2" wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition.

#### **UPRIGHT PADS**

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

#### **NET ANTENNA AND TAPE**

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 ½" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

#### **AVAILABLE OPTIONS**

Center Post Uprights for multi-court applications  
Referee Stand with optional padding  
Storage Cart

Subject to design change and current manufacturing practices.  
Revised April 4, 2008 ©2008 Gared Holdings, LLC