



REVISION		
REV.	DATE	BY
-	-	-



Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

ABOVE FLOOR CENTER BASE SLEEVE

DRAWN	DWP	DATE	8/8/08	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	08/09/08	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	6408
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NOTED	1 OF 1	6408	-	



MODEL 6408
VOLLEYBALL X-BASE

RECOMMENDED APPLICATION

Designed for use in facilities where a sub-floor structure is not adequate to accommodate the installation of a floor sleeve.

SPECIFICATIONS

X-base shall be constructed of welded steel capable of accepting a 4" diameter volleyball post. The gross dimensions will be 12" high x 16.25 "long x 16.25" wide. X-base is securely locked in place with set of 1/2" threaded rod with hand knob screwed into a 1/2" diameter, 13 thread per inch, floor anchor (choose anchor from below). Rubber pads protect floor from damage.

Floor Anchors

Style B – For wood floors installed directly over concrete

Style BX – For wood floors installed directly over concrete, except knurled anchor has been extended to 3-1/4"

Style C – For concrete floors or synthetic floors installed directly over concrete

Style E – For floating wood floors resting on sleepers or metal clip fasteners

Optional X-Base Padding

6060 – Center X-base pad

Colors available are white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, dark blue, gray, black, maroon, beige, teal and purple.