



REVISION		
REV.	DATE	BY
-	-	-




Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

COLLEGIATE VOLLEYBALL SYSTEM - 3 COURT

DRAWN	RWP	DATE	06/17/08	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	06/18/08	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	7203
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NONE	1 OF 1	7203	-	



MODEL 7203

THREE COURT COLLEGIATE VOLLEYBALL SYSTEM

RECOMMENDED APPLICATION

Top quality unit for use in facilities requiring product for multi-use functions. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

FLOOR SLEEVES AND COVER PLATES

Please refer to attached specification

UPRIGHTS

System shall be supplied with one winch post, two center winch posts, and one end post. Upright posts shall be 6063-T6 aluminum, 4" Diameter, 9'-6" length, post with a weight of 25 lbs. Finish shall be gray anodized. Upright posts shall be removable type with sleeves and covers and permanent fixture to the floor. Net heights shall be achieved by sliding aluminum adjustable rails to desired net height and locking rails in place with wedge type locking mechanism. Adjustable rails shall slide the full length of the post. Upright posts shall have high impact plastic caps on ends of the posts for floor protection.

NET TENSIONER (WINCH)

The net tensioner shall incorporate a heavy duty, self-locking ratchet mechanism with a compression clutch brake type release. A high tensile nylon strap will be used with the winch to achieve required net tension.

NET

Net features include 1" diameter wood dowel and 4" square black nylon mesh (250-lbs tensile strength) for excellent performance and durability. Free floating net along 1/8" diameter steel 7 x 19 cable (1,760-lbs. Minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with metallic clips are used to secure net in place. Net shall be 32' length and 39" width. Net perimeter shall have a 2" wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition.

UPRIGHT PADS

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

NET ANTENNA AND TAPE

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

AVAILABLE OPTIONS

Referee Stand with optional padding
Storage Cart

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC