



REVISION		
REV.	DATE	BY
-	-	-



Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

72" ACRYLIC CONVERSION BACKBOARD

DRAWN	CONNERLEY	DATE	07/11/08	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	07/11/08	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	BB72A38-ARG
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NOTED	1 OF 1	BB72A38-ARG	-	



MODEL BB72A38-ARG

STEEL FRAME 72" X 42" RECTANGULAR ACRYLIC BACKBOARD WITH BUILT IN ADAPTER FOR 35" X 20" MOUNTING

Backboard shall be constructed of a unitized welded tubular frame utilizing heavy wall $\frac{3}{4}$ " x 1.5" rectangular steel tubing. Frame shall include two vertical struts on 35 inch centers with adapter brackets for mounting to support structure with fan shaped board mounting centers. Design shall provide a reinforced goal mounting area to allow for direct mounting of goal, board, and structure if required.

Adapter brackets shall be positioned at 20" vertical and 35-1/4" horizontal centers for mounting backboard with standard fan-shaped mounting dimensions.

Backboard surface shall be constructed of 3/8" thick clear acrylic treated for UV protection, and abrasion resistance. Goal mounting holes shall be on standard 5" horizontal and 5" vertical centers.

Board frame shall be powder coated separately with a flat black weather resistant finish before being assembled.

GOALS

Compatible goals are models 8550, 5500, 8800, 7550, 240, and 39WO. See goal section in specification manual.

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC