



MODEL FGP602P

COLLEGIATE FOOTBALL GOAL POST 5' OFFSET Permanent Adjustable Plate Mounting

This unit uses a gooseneck design to meet all NCAA specs. Goal measures 30' high with a 6' offset. Crossbar measures 18'-6" between uprights. Gooseneck post is 5 9/16" O.D. powder coated over galvanized steel. Crossbar is 4 1/2" O.D powder coated over galvanized steel. Uprights are 2 3/8" O.D powder coated over galvanized steel. Uprights measure 20' above crossbar. Wind flags are included.

Unit shall be designed for permanent installation. Upright mounting anchors to be installed in a concrete footing approximately 42" in diameter and 60" deep. Post shall mount with the use of four 3/4" diameter threaded anchors through the lower post plate.

This model goal post is not compatible with ground sleeves.

Concrete for installation not included.

Colors are selected by specifying one of the part numbers listed below on the order.

FGP602PW	White gooseneck, crossbar and upright
FGP602PY	Yellow gooseneck, crossbar and upright

Optional Equipment

GSPPAD4	Protective post pad for posts up to 6" O.D.
---------	---

Protective pads are 6' high for installation around post areas where body contact may occur. Constructed of high density urethane foam covered with 18 oz. mildew resistant and UV resistant coated vinyl. Available in the following colors: red, white, green, yellow, royal blue, black, purple, orange, and gray.

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC