



## MODEL FGP602S

### HIGH SCHOOL FOOTBALL GOAL POST 5' OFFSET

This unit uses a gooseneck design to meet all NCAA specs. Goal measures 30' high with a 6' offset. Crossbar measures 18'-6" between uprights. Gooseneck post is 5 9/16" O.D. powder coated over galvanized steel. Crossbar is 4 1/2" O.D powder coated over galvanized steel. Uprights are 2 3/8" O.D powder coated over galvanized steel. Uprights measure 20' above crossbar. Wind flags are included.

Unit shall be designed for permanent installation. Upright to be installed with a concrete footing approximately 42" in diameter and 60" deep. Post shall extend approximately 42" into concrete footing.

Semi permanent installation can be achieved with the use of optional ground sleeves. Ground sleeves shall be installed in concrete footing as described in specification FGP600GS.

**Concrete for installation not included.**

**Colors are selected by specifying one of the part numbers listed below on the order.**

FGP602SW	White gooseneck, crossbar and upright
FGP602SY	Yellow gooseneck, crossbar and upright

#### **Optional Equipment**

GSPPAD4	Protective post pad for posts up to 6" O.D.
---------	---

Protective pads are 6' high for installation around post areas where body contact may occur. Constructed of high density urethane foam covered with 18 oz. mildew resistant and UV resistant coated vinyl. Available in the following colors: red, white, green, yellow, royal blue, black, purple, orange, and gray.