



REAR VIEW

FRONT VIEW

| REVISION | | |
|----------|----------|-----|
| REV. | DATE | BY |
| A | 06/17/08 | JJC |
| | | |
| | | |
| | | |
| | | |
| | | |



Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

72" ACRYLIC RESIDENTIAL BACKBOARD

| | | | | | |
|---|-----------|----------|----------|----------|---------|
| DRAWN | CONNERLEY | DATE | 12/02/06 | MATERIAL | N/A |
| APPROVED | JJC | DATE | 12/02/06 | FINISH | N/A |
| FILE LOC. Q:\Final Release\Specifications | | | | DWG. NO. | GP72422 |
| SIZE | SCALE | SHT. NO. | PART NO. | REV | A |
| A | NOTED | 1 OF 1 | GP72422 | A | |



MODEL GP72422

STEEL FRAME 72" X 42" RECTANGULAR ACRYLIC BACKBOARD

Backboard shall be constructed of a unitized welded tubular frame utilizing heavy wall 1" x 2" rectangular steel tubing. Frame shall include two vertical struts on 35 inch centers with holes for mounting to support structure. Design shall provide for a reinforced area for goal mounting.

Backboard shall be designed for use with residential adjustable units.

Backboard surface shall be constructed of 3/8" thick clear acrylic treated for UV protection, and abrasion resistance. Goal mounting holes shall be on standard 5" horizontal and 5" vertical centers.

Board frame shall be powder coated separately with a flat black weather resistant finish before being assembled.

GOALS

Compatible goals are models 726, and 1000. See goal section in specification manual.