



REAR VIEW

FRONT VIEW

NOTE:
 BACKBOARD THICKNESS - 2 1/8".
 MATERIAL - 1/2" THICK TEMPERED GLASS WITH STEEL FRAME.
 FINISH - GRAY POWDERCOAT ON BRACKETS AND PLATES.

REVISION		
REV.	DATE	BY
A	12/01/03	JJC
B	06/06/08	RWP
C	06/08/09	RWP



Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

42" STEEL FRAME GLASS BACKBOARD				
DRAWN	CONNERLEY	DATE	05/02/03	MATERIAL AS NOTED
APPROVED	JJC	DATE	05/02/03	FINISH AS NOTED
FILE LOC.	Q:\Final Release\Specifications			DWG. NO. LXP4200
SIZE	SCALE	SHT. NO.	PART NO.	REV
A	NOTED	1 OF 1	LXP4200	C



MODEL LXP4200

STEEL FRAME 72" X 42" RECTANGULAR GLASS BACKBOARD

The LXP4200 backboard shall be fabricated with steel frame constructed of formed steel angles, former and fastened together and connected with heavy gauge steel mounting plates to reinforce corners. The lower horizontal frame section shall have a tubular steel support brace for added strength. Manufacturer of backboard shall have over ten years of experience producing such item. Backboard shall meet NCAA and high school requirements.

Entire frame and components shall be powder coated with a durable neutral gray finish. Acrylic cushioning pad shall be used between steel mounting plate and glass to protect board against possible breakage.

Glass shall be ½" in thickness and fully tempered with white target lines permanently fused onto the surface. 12mm glass will not be considered equal to ½" glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full ½" glass. Vinyl shock absorbing material insulates the glass from the frame. Goal mounting holes shall be on standard 5" horizontal and 4" vertical centers.

ACCESSORIES

GOALS

Compatible goals are models 1000, 2000+, 2500, 2500I, 3000, 20123T-B (Snap B), and 5500. See goal section in specification manual.

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC