



NOTE:
 BACKBOARD THICKNESS - 2 1/8".
 MATERIAL - 1/2" THICK TEMPERED GLASS WITH STEEL FRAME.
 FINISH - GRAY POWDERCOAT ON BRACKETS AND PLATES.

REVISION		
REV.	DATE	BY
A	12/01/03	JJC
B	06/06/08	RWP
C	06/08/09	RWP



Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

48" STEEL FRAME GLASS BACKBOARD				
DRAWN	CONNERLEY	DATE	05/02/03	MATERIAL AS NOTED
APPROVED	JJC	DATE	05/02/03	FINISH AS NOTED
FILE LOC.	Q:\Final Release\Specifications			DWG. NO. RG
SIZE	SCALE	SHT. NO.	PART NO.	REV
A	NOTED	1 OF 1	RG	C



MODEL RG

STEEL FRAME 72" X 48" RECTANGULAR GLASS BACKBOARD

The RG backboard shall be fabricated with a steel frame constructed of formed steel angles, formed and fastened together and connected with heavy gauge steel mounting brackets to reinforce corners. Manufacturer of backboard shall have over ten years experience producing such item. Backboard shall meet NCAA and high school requirements.

Entire frame and components shall be powder coated with a durable neutral gray finish. Shock insulating pads shall be used between steel goal mounting plate and glass to protect board against possible breakage.

Glass shall be ½" in thickness and fully tempered with white border and target lines permanently fused onto surface. 12mm glass will not be considered equal to ½" glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full ½" glass. Vinyl shock absorbing material shall insulate glass from frame. Goal mounting holes shall be on standard 5" horizontal and 5" vertical centers.

ACCESSORIES

GOALS

Compatible goals are models 1000, 2000+, 2500, 3000, 20123T-A (Snap A), and 5500. See goal section in specification manual.