



DIMENSIONS BELOW ARE ± 1/2"

TRUSS HEIGHT FEET & (METERS)	DIM "A" Ft.-In. (Meters)	DIM "B" Ft.-In. (Meters)
18' TO 19.9' (5.48-6.09M)	4'-7" (1.40M)	3'-0" (.91M)
20' TO 21.9' (6.10-6.70M)	5'-5" (1.65M)	4'-0" (1.22M)
22' TO 23.9' (6.71-7.31M)	6'-8" (2.03M)	5'-0" (1.52M)
24' TO 25.9' (7.32-7.92M)	7'-11" (2.41M)	6'-0" (1.83M)
26' TO 27.9' (7.93-8.52M)	9'-0" (2.74M)	7'-0" (2.13M)
28' TO 30.0' (8.53-9.14M)	10'-8" (3.25M)	8'-0" (2.44M)

**NOTE:**  
 STANDARD ATTACHMENT HEIGHTS (TRUSS HEIGHT) FOR MODEL 3305 WELDED UNITS ARE 18 FT. MINIMUM TO 30 FT. MAXIMUM.  
 CONTACT PERFORMANCE SPORTS SYSTEMS FOR INFORMATION IF TRUSS HEIGHTS ARE NOT WITHIN THIS RANGE.

REVISION		
REV.	DATE	BY
A	05/19/08	RWP



**PSS**  
PERFORMANCE  
SPORTS SYSTEMS



**G**  
GARED™

**Gared Holdings, LLC**  
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

**REAR BRACED, ROLL FOLD BACKSTOP - WELDED**

DRAWN	SNOW	DATE	10/26/05	MATERIAL	N/A
APPROVED	ATS	DATE	10/26/05	FINISH	N/A
FILE LOC.	Q:\Final Release\Specifications			DWG. NO.	3305
SIZE	SCALE	SHT. NO.	PART NO.		
<b>A</b>	NONE	1 OF 1		<b>3305</b>	<b>A</b>



## MODEL 3305

### **WELDED SINGLE POST REAR BRACED ROLL-FOLD BACKWARD FOLDING BASKETBALL STRUCTURE**

#### **RECOMMENDED APPLICATION**

This unit is designed for applications requiring the backstop to backward fold away from the court lines in a minimal space. This single post unit can be used at heights from 18' to 30'.

#### **SPECIFICATIONS**

##### **SUPERSTRUCTURE**

Unit shall be supported from 3-1/2" O.D. x 0.120" wall ASTM A-500 Grade B horizontal and 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 vertical structural steel tubing secured to the building with heavy gauge steel stampings or weldments (as required by building conditions). When truss span widths exceed 10'-0", 3-1/2" O.D. x Schedule 40 (0.216") wall ASTM A-500 Grade B will be used for the horizontals. Spans over 14'-0" will use welded bridge pipe.

##### **BACKSTOP**

The backstop shall be of a single post design with a main vertical mast made of 6-5/8" O.D. x 0.120" wall ASTM A-500 Grade B structural steel tubing with 2-1/2" x 1-1/2" x 14 gauge (0.083") wall ASTM A-513 rectangular steel tube sway braces miter cut and welded in place to a top horizontal 4" x 1-1/2" x 0.18" web ASTM A-36 steel channel. Main mast will be suspended from superstructure with an offset hanger 3" in front of the pivot point. Units with less than 3" offset will not be approved as equal. Backstop shall be manufactured to allow 6" vertical adjustment for plumbing of the backboard. All fittings shall be heavy gauge steel stampings or weldments. A direct goal attachment is used to transfer stress from the goal to the main mast assembly preventing strain on the backboard. An adjustable suspension hanger shall be mounted on a special carrier system to roll forward on a slope track system allowing the vertical mast to roll forward while the backstop is being raised. The carrier-hanger system will fully encompass the track system for maximum strength and stability. All fittings shall be heavy gauge steel stampings or weldments. A direct goal attachment is used to transfer stress from the goal to the main mast assembly preventing strain on the backboard.

Rear brace shall be 1-7/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tubing attached to the main mast 12" to 18" above bottom of mast pipe. When truss heights are higher than 23'-0", front brace shall be 2-3/8" O.D. x 12 gauge (0.109") wall ASTM A-513 steel tubing. Folding brace shall be of a jackknife design with an adjustable hinge for easy installation and field adjustment. Backstop shall be raised and lowered with 1/4" galvanized aircraft cable with a breaking strength of 7000 lbs. Backstop shall be furnished with standard black finish. If special finish coat is required, specify final painting by painting contractor. Backstop manufactured in accordance with 1994 rule 1, section 8, stating that all parts of the backboard support system shall be at least 6" behind backboard.

##### **ACCESSORIES**

##### **BACKBOARDS AND GOALS**

All PSS and/or Gared backboards and goals are available on this unit. See the backboards and goals section in the specification manual.

##### **BANK PADDING**

See the accessories section in the specification manual.

##### **HOISTS**

Either Electric hoist or manual winch is available on all folding units. See the accessories section in the specification manual.

Subject to design change and current manufacturing practices.  
Revised April 4, 2008 ©2008 Gared Holdings, LLC