



REAR VIEW

FRONT VIEW

(2) HOLES FOR 3/8" CARRIAGE BOLTS WHEN USED AS DIRECT MOUNT

Ø0.44 [11.1mm] (4) HOLES

REVISION		
REV.	DATE	BY
A	06/06/08	RWP



Gared Holdings, LLC  
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

72" GLASS MULTIPURPOSE BACKBOARD				
DRAWN	CONNERLEY	DATE	12/02/06	MATERIAL N/A
APPROVED	JJC	DATE	12/02/06	FINISH N/A
FILE LOC. Q:\Final Release\Specifications			DWG. NO.	BB72G50
SIZE	SCALE	SHT. NO.	PART NO.	REV
A	NOTED	1 OF 1	BB72G50	A



## **MODEL BB72G50**

### **STEEL FRAME 72" X 42" RECTANGULAR GLASS BACKBOARD**

Backboard shall be constructed of a unitized welded tubular frame utilizing heavy wall  $\frac{3}{4}$ " x 1.5" rectangular steel tubing. Frame shall include two vertical struts on 35 inch centers with holes for mounting to support structure. Design shall provide a reinforced goal mounting area to allow for direct mounting of goal, board, and structure. Direct mounting design shall have integral holes to allow permanent attachment of board to post and allow for goal replacement without removing the board.

Backboard shall be designed for use with residential adjustable units, gooseneck posts, and straight arm posts.

Glass shall be  $\frac{1}{2}$ " in thickness and fully tempered with white target lines permanently fused onto the surface. 12mm glass will not be considered equal to  $\frac{1}{2}$ " glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full  $\frac{1}{2}$ " glass. Vinyl shock absorbing material insulates the glass from the frame. Goal mounting holes shall be on standard 5" horizontal and 5" vertical centers.

Board frame shall be powder coated separately with a flat black weather resistant finish before being assembled.

#### **GOALS**

Compatible goals are models 8550, 5500, 8800, 7550, 240, and 39WO. See goal section in specification manual.