





Gared Holdings, LLC 9200 E. 146th St. Noblesville, IN 46060 THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

LOOP STYLE BIKE RACK							
DRAWN RWP DATE 06/20/08			E 06/20/08	MATERIAL N/A			
APPROVED CONNERLEY DATE 06/20/08				FINISH N/A			
FILE LOC	Q:\Final	Release\Spe	ecifications		DWG. NO.	BRL5	
SIZE	SCALE	SHT. NO.	PART NO.				REV
A NOTED 1 OF 1 BRL5						-	





## **MODEL BRL5**

## **LOOP STYLE RACK – 11 BIKE CAPACITY**

Bike rack shall be constructed of 2 3/8" [60.3 mm] O.D. x 0.156" [4.0 mm] wall galvanized steel tubing. Tubing shall be formed from one continuous length. Ends of bike rack shall extend 10" [254 mm] into concrete footings that are 10" [254 mm] minimum diameter x 15" [381 mm] minimum deep for permanent mounting.

Standard finish is galvanized. Optional powder coat finishes available in black, bronze, blue, red, or green. Powder coat finishes applied over galvanized base tube for durable outdoor resistance to the elements.

Capacity of the rack shall be 11 bicycles.

Concrete for installation not included.