



SCOREBOARD SPECIFICATIONS

MODEL GS-335

Lead your league with this Baseball/Softball scoreboard! Large 15" high super-bright 100,000-hour rated LED numerals are the largest with the widest viewing angle in the industry and are visible over 300 feet. The 22-gauge galvanized steel cabinet with powder-coat finish means your scoreboard is the most durable on the market and will look brand new for many years! Scoreboard package includes: operator's keyboard, digit protective shields, junction box cover (cable models only), mounting rails and a complete operation, installation, service manual and warranty details on the CD shipped with the scoreboard.

OVERALL DIMENSIONS

14' wide x 5'6" tall x 8.0" depth

WEIGHT

Hanging weight: 380 lbs.
Shipping weight: 500 lbs.

CONSTRUCTION

22-gauge galvanized steel cabinet with powder coat finish for strength, durability, and lasting appearance

POWER REQUIREMENTS

Scoreboard:

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

Controller:

Standard LCD controller powered by 12V DC Adapter or an optional internal battery.

SCORING INFORMATION DISPLAYED

HOME AND GUEST: Home 2-Digit and 1 dot, Guest 2-digit and 1 dot

BALL: 3-dot display

STRIKE: 2-dot display

OUT: 2-dot display

HITS: dot

ERRORS: dot

RUNS: 2-digit displays, 0-99, Home and Guest

INN: 2-digit display 0-99

Time of day clock: 2-2digits display 00:59-00:00 and 12:00-

CAPTIONS

HOME and GUEST: 12.0" tall

BALL, STRIKE, H-E and OUT: 11.0" tall

POSS ARROW: 4.0" tall

INN: 9" tall

COLON DOTS: 3.0" tall

Polymeric Calendared Vinyl Lettering

TOD CLOCK, GUEST and HOME, and INNING Displays

15.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays

Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

BALL,STRIKE, OUT H/E and Colon: Displays

2" dot, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays

APPROVALS

ETL/CSA listed

Scoreboard: Meets all FCC Class A requirements

2.4 GHz wireless transmitter: FCC Part 15 certified

2.4 GHz wireless receiver: Meets all FCC Part 15 requirements

WARRANTY

This product is warranted against defects in materials and workmanship for the period specified in the warranty from the date of invoice.

INSTALLATION

This model may be installed between (2) 8" OD steel, schedule 40 poles; or (2) 8" I-beams, minimum. Hole depth

/diameter as well as pole/concrete specifications must be based on customer's local building codes, soil conditions, and wind loads. Mounting rails are supplied.

Support structure and mounting hardware supplied by installer/others

SCOREBOARD CONTROLLER

Dimensions: 2.5" height x 14.0" width x 7.0" depth. **Weight:** 2.10 lbs.

The keyboard controller available with this scoreboard is microprocessor-controlled, molded of high-impact ABS plastic, has a tactile membrane keypad. Options include 2.4 GHz wireless control and internal battery pack with automatic battery charger.

Cable-Controlled System (standard) Includes:

- (1) Keyboard controller
- (3) BASEBALL/SOFTBALL keypad inserts
- (1) Junction box cover with receptacle (to be installed at scorekeeper's location)
- (1) 20-ft. signal cable (used to connect the keyboard to the junction box receptacle)
- (1) Project-specific length of 4 wire twisted pair, shielded control cable

2.4 GHz Wireless System (optional) Includes:

- (1) Universal LCD keyboard controller
- (3) BASEBALL/SOFTBALL keypad inserts
- (1) 12-volt DC wall transformer for standard model
- (1) 2.4 GHz transmitter (built into the LCD keyboard controller)
- (1) 2.4 GHz receiver (connects to the scoreboard, eliminating control cable and junction box installation)

OPTIONS

Wireless Remote Control System
Controller Carrying Case
Wireless Remote Control Battery Option
Sponsor Panels
Solar-Charged Battery Power
Horn
Electronic Team Names
Football Conversion Kit
Message Center
Soccer Conversion Kit